



DOME FLANGE										
RIVET SIZE	PART #	RIVET LENGTH L mm	GRIP RANGE G mm	M mm	D mm	H mm	F mm	A mm	N mm	Y MAX mm
4.0 mm 5/32	SAA52RB	13.6	1.0-3.0	2.31	4.00	1.4	8.00	48	16.0	6.0
	SAA54RB	18.8	1.0-7.0	2.31	4.00	1.4	8.00	53	20.4	8.5
4.8 mm 3/16	SAA64RB	15.3	1.0-4.0	2.91	4.82	1.8	9.8	51	18.3	7.0
	SAA66RB	20.5	1.0-9.0	2.91	4.82	1.8	9.8	56	23.5	9.5
	SAA68RB	24.0	4.0-12.0	2.91	4.82	1.8	9.8	60	27.0	11.0
LARGE FLANGE										
4.8 mm 3/16	SAB63RB	15.3	1.0-4.0	2.91	4.82	2.0	14.0	51	18.3	7.0
	SAB64RB	17.5	1.0-6.3	2.91	4.82	2.0	14.0	53	20.5	8.0
	SAB66RB	20.5	1.0-9.0	2.91	4.82	2.0	14.0	56	23.5	9.5

RIVET SIZE	RECOMMENDED HOLE SIZE	TYPICAL SHEAR STRENGTH N/Kgf	TYPICAL TENSILE STRENGTH N/Kgf
4.0 mm	4.2-4.5	600/61	1000/102
4.8 mm	5.0-5.3	900/92	1200/122

Product specification are in effect at the time of publishing